

SABRE COVER

Compatible with Indala®** Classic
Wall Switch Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	Indala®** Classic Wall Switch Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from Indala®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with Indala®** Classic
Mullion Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	Indala®** Classic Mullion Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from Indala®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with Indala®** Classic Keypad Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	Indala®** Classic Keypad Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from Indala®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with Identiv® TS
Mullion Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	Identiv® TS Mullion Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Casi®, and Honeywell®
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** Proximity
ThinLine II®** Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID®** Proximity ThinLine II®** Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** Proximity
ProxPoint®** Plus Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID®** Proximity ProxPoint®** Plus Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** MiniProx®**
Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID®** MiniProx®** Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** iCLASS
SE®** RP40 Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID® iCLASS SE®** RP40 Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** iCLASS
SE®** RP15 Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID®** iCLASS SE®** RP15 Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.



SABRE COVER

Compatible with HID®** iCLASS
SE®** RP10 Readers



Tech Specs

Description	The Safetrust SABRE COVER is clip-on upgrade that acts as a Bluetooth Low Energy (BLE) to RFID gateway module.
Compatible With	HID®** iCLASS SE®** RP10 Readers
Hardware	Bluetooth Low Energy (2.400 GHz - 2.4835 GHz), proximity 125 kHz
Bluetooth Range	1 ft to 50 ft (.31 to 15 meters)
Compatibilities (with host reader)	Most popular 125kHz proximity formats from HID®**
COVER Compatibilities	Most popular 125kHz proximity formats from HID®**, Indala®**, AWID®, GE Cas i®, and Honeywell®
Mounting	Reader specific clip-on
Mobile Operating Systems	Apple iOS 9.0 or later, Android 4.1 or later on devices with the Safetrust Wallet
Encryption	AES 256, x.509
Power Source	RFID field (no battery required)
Operating Conditions:	Temperature: -31 to 149°F (-35 to +65°C) Humidity: 5-95% (non-condensing)
Warranty	2 Years (limited warranty, review warranty for complete details)

*Technical data subject to change without notice. To order, contact sales@safetrust.com or visit www.safetrust.com/shop.

